



GL609C

HPPE | Nitrile | Sandy

ANSI/ISEA 105-2016 – CUT A6 | ABRASION 6 | PUNCTURE 4

ANSI/ISEA 138-2019 – IMPACT 2

EN388: 2016 – 4X43EP

Nitrile sandy palm coating // 13 gauge HPPE liner //
Reinforced thumb // TPR // Good grip in all conditions //
Extra absorption

GL609C S – 2XL

Suggested Applications

Steel Handling + Fabrication // Glass Handling // Mining
// Oil + Gas // HVAC // Warehousing // Automotive

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Sandy
Liner: 13 Gauge HPPE
TPR: Thermo Plastic Rubber
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

EN388: 2016 – 4X43EP

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				

ANSI/ISEA 138-2019

Impact	1	2	3
--------	---	---	---



i Product markings may vary. Refer to the product sheet for the most current test report results.

Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Sold Individually
Pack: 6 pair
Case: 60 pair
Country of Origin: China