

# Neshoba™

ANSI/ISEA Z87.1-2020 | CAN/CSA Z94.3-2020 | CE/UKCA EN 166

Frameless design with thin flexible temples // Ultra lightweight spectacle - 16 gm

## VARIATIONS

Lens and Temples | 6 Variations

- ES9710S Clear
- ES9710ST Clear **H2X AF**
- ES9720S Grey
- ES9720ST Grey **H2X AF**
- ES9780S I/O Mirror
- ES9780ST I/O Mirror AF



### General Specifications

Weight: 16 gm  
 PD: 64 mm  
 Bridge: 12.3 mm  
 Lens base: 9.5 curve  
 Lens size diagonal: 75.8 mm  
 Lens size vertical: 43.3 mm  
 Lens thickness: 1.6 mm  
 Overall length (lens - tip): 151 mm  
 Overall width (hinge - hinge): 135 mm  
 Closest point between lens: 14.5 mm

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special Purpose  
**UV Filter Transmittance**  
 U6: .01% max effective far UV • .1% max near UV  
**Visible Light Filters**  
 L1.7: 55% max. visible light  
 L2.5: 29% max visible light

### Part No.

S9710S  
 S9710ST  
 S9720S  
 S9720ST  
 S9780S  
 S9780ST

### Lens Marking

P Z87 + U6  
 P Z87 + U6  
 P Z87 + U6 L2.5  
 P Z87 + U6 L2.5  
 P Z87 + U6 L1.7  
 P Z87 + U6 L1.7

### Temple Marking

P Z87 + / P c SEI CAN/CSA Z94.3-15  
 P Z87 + / P c SEI CAN/CSA Z94.3-15  
 P Z87 + / P c SEI CAN/CSA Z94.3-15  
 P Z87 + / P c SEI CAN/CSA Z94.3-15  
 P Z87 + / P c SEI CAN/CSA Z94.3-15  
 P Z87 + / P c SEI CAN/CSA Z94.3-15

### Materials

Lens: polycarbonate  
 Temples: polycarbonate  
 Hinge: polycarbonate  
 Screw: stainless steel

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

Product markings may vary // Updated as of 03.26