

# Outlander™

Sporty dual frame style with wide temples



#### Black Frame

Part	Lens
SB8010D•	Clear
SB8020D•	Gray
SB8065D•	Ice Blue Mirror
SB8070D•	Silver Mirror
SB8080DT•	Indoor/Outdoor Mirror Anti-Fog

#### Caramel Mixed Frame

Part	Lens
SCM8018D•	Sandstone Bronze
SCM8020D•	Gray

#### Nickel Frame

Part	Lens
SNK8020D•	Gray
SNK8070D•	Silver Mirror

- Sporty dual lens style with wide temples provides full eye protection against high impact.
- Suitable for both working environments and sports activities.
- Soft nose piece provides comfort for extended use without slipping.
- Polycarbonate lens filter out 99.9% of harmful UV rays.

#### GENERAL SPECIFICATION

Bridge: 10.2mm
Closest Point Between Lens: 17.7mm
Closest Point Between Temples Tips: 89mm
Lens Base: 8 Curve
Lens Size Diagonal: 58mm
Lens Size Vertical: 40.5mm
Lens Thickness: 2.2mm
Overall Length (Lens-Tip): 158mm
Overall Width (Hinge- Hinge): 127.5mm
PD: 68mm
Weight: 32gm

## PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve, dual lens frame style
Frame	PC+PET	Wrap around design with wide temples for extended side protection
Nose Piece	PVC	Glued onto the nose bridge, pillow softness
Temple	PC+PET	Spatula Type
Hinge	Polycarbonate	3 barrel type, integral to frame/temple
Screw	Stainless Steel	Standard Hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8010D	 Clear	P Z87 + U6	P Z87 +
SB8020D	 Gray	P Z87 + U6 L2.5	P Z87 +
SB8065D	 Ice Blue Mirror	P Z87 + S	P Z87 +
SB8070D	 Silver Mirror	P Z87 + S	P Z87 +
SB8080DT	 Indoor/Outdoor Anti-Fog	P Z87 + S	P Z87 +
SCM8018D	 Sandstone Bronze	P Z87 + S	P Z87 +
SCM8020D	 Gray	P Z87 + U6 L2.5	P Z87 +
SNK8020D	 Gray	P Z87 + U6 L2.5	P Z87 +
SNK8070D	 Silver Mirror	P Z87 + S	P Z87 +

## LENS MARKING

### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

### UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

### Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

## FRAME MARKING

### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact