

PMXSLIM®

ANSI/ISEA Z87.1-2020 + | CE/UKCA EN 166

Slim fit for smaller facial features // Soft adjustable nose piece // Co-injected temple design includes soft rubber tips for a non-slip fit // Custom imprinting available



VARIATIONS

Black Temples | 4 Variations

- SB7110S Clear
- SB7110ST Clear **H2X AF**
- SB7120ST Gray **H2X AF**
- SB7138S Sandstone Bronze

Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB7110S	P Z87 + U6	P Z87 +	Weight: 25 gm	Lens: polycarbonate
SB7110ST	P Z87 + U6	P Z87 +	PD: 68 mm	Frame: polycarbonate
SB7120ST	P Z87 + U6 L2.5	P Z87 +	Bridge: 14.5 mm	Temples: polycarbonate & thermoplastic elastomers
SB7138S	P Z87 + S	P Z87 +	Lens base: 10 curve	Hinge: polycarbonate
			Lens size diagonal: 137.7 mm	Screw: stainless steel
			Lens size vertical: 45 mm	Side shields: polycarbonate
			Lens thickness: 2.3 mm	Nosepiece: polyvinyl chloride
			Overall length (lens - tip): 170 mm	
			Overall width (hinge - hinge): 129 mm	
			Closest point between lens: 9 mm	

Lens Marking Symbols	Temple Marking Symbols
P: Manufacturer's mark	P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices	Z87: ANSI standard for eye and face protection devices
+: High impact	+: High impact
S: Special purpose	

UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Visible Light Filters
 L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Product markings may vary // Updated as of 03.26