

# Rendezvous® ANSI • CE • Ballistic •



Adjustable nose piece // Temples adjust to four different lengths // Lens angle aligns to proper position for work application with ratcheting lens pitch adjustment // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

## Black Frame | 6 Variations

- SB2810S ●●● Clear
- SB2810ST ●●● Clear **H2X AF**
- SB2820S ●●● Gray
- SB2820ST ●●● Gray **H2X AF**
- SB2830S ●●● Amber
- SB2880S ●●● I/O Mirror



SCG28

## Crystal Gray Frame | 1 Variation

- SCG2810ST ●●● Clear **H2X AF**

Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB2810S	P + U6	P Z87 +	Weight: 28 gm	Lens: polycarbonate
SB2810ST	P + U6	P Z87 +	PD: 68 mm	Frame: polycarbonate
SB2820S	P + U6 L2.5	P Z87 +	Bridge: 9.6 mm	Temples: polycarbonate
SB2820ST	P + U6 L2.5	P Z87 +	Lens base: 9.5 curve	Hinge: polycarbonate
SB2830S	P + U6	P Z87 +	Lens size diagonal: 83 mm	Screw: stainless steel
SB2880S	P + U6 L1.7	P Z87 +	Lens size vertical: 45.5 mm	Nose Piece: polycarbonate
SCG2810ST	P + U6	P Z87 +	Lens thickness: 2.42 mm	
			Overall width (hinge - hinge): 138 mm	
			Closest point between lens: 75-76 mm	

### Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special Purpose

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact