



# Ridgeline® Cap Style

ANSI • CSA • (with clip only)

Shell constructed from ABS material // Low profile design // Available with 4- point and 6-point ratchet suspensions // Swinging hinge points // 4-position harness // Adjusts from 6½ to 8 // Rear padded suspension // Replacement suspensions available // Vented pressure pad // Universal accessory slots // Passes Reverse Orientation, High-Temperature (HT) and Low Temperature (LT) // Vented cap style hard hats are rated Class C and do not meet Class E or G safety standards // Custom imprinting available



## Vented Cap Style

4-Point Ratchet | 7 Variations

- HP44110V • White
- HP44112V • Gray
- HP44120V • Red
- HP44130V • Yellow
- HP44131V • Hi-Vis Lime
- HP44141V • Hi-Vis Orange
- HP44160V • Blue



## Standard Cap Style

4-Point Ratchet | 15 Variations

- HP44110 • White
- HP44110C • White
- HP44112 • Gray
- HP44113 • Slate Gray
- HP44120 • Red
- HP44130 • Yellow
- HP44130C • Yellow
- HP44131 • Hi-Vis Lime
- HP44131C • Hi-Vis Lime
- HP44135 • Green
- HP44141 • Hi-Vis Orange
- HP44160 • Blue
- HP44162 • Light Blue
- HP44165C • Dark Blue
- HP44170 • Hi-vis Pink

6-Point Ratchet | 7 Variations











- HP46110 • White
- HP46120 • Red
- HP46130 • Yellow
- HP46131 • Hi-Vis Lime
- HP46135 • Green
- HP46141 • Hi-Vis Orange
- HP46160 • Blue





## Hydro Dipped


### 4-Point Ratchet Hydro Dipped | 10 Variations

-  HP44116 • Matte White Graphite Pattern
-  HP44116S • Shiny White Graphite Pattern
-  HP44117 • Matte Black Graphite Pattern
-  HP44117C • Matte Black Graphite Pattern (CSA with clip only)
-  HP44117S • Shiny Black Graphite Pattern
-  HP44118 • Matte Copper Pattern
-  HP44119 • Realtree AP® (Matte)
-  HP44121 • Matte Red Pattern
-  HP44122 • Matte Blue Pattern
-  HP44MIX • HP44116 (4), HP44117 (4), HP44118 (4), and HP44119 (4)



## Vented Hydro Dipped

### 4-Point Ratchet Hydro Dipped | 2 Variations

-  HP44116SV • Shiny White Graphite Pattern
-  HP44117V • Matte Black Graphite Pattern



HPRBANDR – Ridgeline Cap Style and Full Brim Hard Hat Sweat Band



HPR441 – 4-point Ratchet Replacement Suspension



HPR461 – 6-point Ratchet Replacement Suspension




### Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)  
 Suspension: high density polyethylene (HDPE) & high impact nylon  
 Sweat band: polyester fabric & polyurethane (PU) foam

### General Specifications

Weight: 358 gm  
 Shell thickness: 2 - 4 mm  
 Dimensions: 28 cm x 22 cm x 15.2 cm  
 Suspension adjust sizing: 6.5 - 8  
 Suspensions: 4-point & 6-point ratchet  
 Styles: vented & non-vented  
 Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15  
 Types: Type 1  
 Classes: non-vented Class E, G, and C | vented Class C  
 Optional features: reverse donning, hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

### Markings

Types: Type 1 offers protection to the top of the head  
 Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection  
 Tested and marked for reverse orientation   
 HV: meets all requirements for high visibility  
 LT: provides protection at low temperatures -22°F  
 HT: provides protection at high temperatures 140°F  
 Date code: indicates month and year when the shell was molded –    
 does not indicate service life

### Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use  
 Never alter or modify the shell or suspension system  
 Inspect the hard hat each time before use and replace if there is ANY sign of damage  
 Replace hard hat after it receives a considerable impact  
 Accessories such as liners have not been tested to the requirement of this standard  
 Clean only with mild soap and lukewarm water  
 Store hard hat in a clean, dry place that is out of direct sunlight  
 Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat  
 Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage