



# Ridgeline® Full Brim ANSI • CSA •

Shell constructed from ABS material // Ratchet suspension is easy to adjust, allowing you to modify the fit while wearing the hat // Available in 4-point and 6-point ratchet suspension // 4-point ratchet suspension may be converted to 6-point ratchet suspension with optional strap (HP6PTSUS) // Replaceable ratchet suspensions available // Replaceable sweat band— padded fabric and polyurethane foam // Passes high temperature (HT) and low temperature (LT) // Custom imprinting available

## Vented Full Brim

4-Point Ratchet Vented | 7 Variations

- HP54110V •• White
- HP54113V •• Slate Gray
- HP54130V •• Yellow
- HP54131V •• Hi-Vis Lime
- HP54141V •• Hi-Vis Orange
- HP54160V •• Blue
- HP54117V •• Matte Black Graphite

## Hydro Dipped

4-Point Ratchet Hydro Dipped | 10 Variations

- HP54116 •• Matte White Graphite Pattern
- HP54116S •• Shiny White Graphite Pattern
- HP54117 •• Matte Black Graphite Pattern
- HP54117S •• Shiny Black Graphite Pattern
- HP54117V •• Matte Black Graphite Pattern (Vented)
- HP54118 •• Matte Copper Pattern
- HP54119 •• Realtree AP® (Matte)
- HP54121 •• Matte Red Pattern
- HP54122 •• Matte Blue Pattern
- HP54MIX •• HP54116 (3), HP54117 (3), HP54118 (3), and HP54119 (3)



## Standard Full Brim

4-Point Ratchet | 11 Variations

- HP54110 •• White
- HP54111 •• Black
- HP54112 •• Gray
- HP54113 •• Slate Gray
- HP54120 •• Red
- HP54130 •• Yellow
- HP54131 •• Hi-Vis Lime
- HP54135 •• Green
- HP54141 •• Hi-Vis Orange
- HP54160 •• Blue
- HP54170 •• Hi-Vis Pink

6-Point Ratchet | 5 Variations

- HP56110 • White
- HP56120 • Red
- HP56130 • Yellow
- HP56135 • Green
- HP56160 • Blue



REALTREE AP © 2013 of Jordan Outdoor Enterprises, Ltd., all rights reserved.

P 800.736.8673 // F 901.861.4967 // W PYRAMEXSAFETY.COM

Ridgeline standard and hydro dipped head protection meets ANSI Z89.1 (•) Type 1 Class E, G, and C. Ridgeline vented head protection meets ANSI Z89.1 Type 1 Class C. Options also meet Canadian CSA Z94.1-2015 (•) standards. Hi-vis colors have been tested for the "HV" mark.



HPR541 — 4-Point Ratchet Replacement Suspension



HP6PTSUS — 6-Point Suspension Strap



## Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)  
Suspension: high density polyethylene (HDPE) & high impact nylon  
Sweat band: polyester fabric & polyurethane (PU) foam

## General Specifications

Weight: 378 gm  
Shell thickness: 1.7 - 4 mm  
Dimensions: 31 cm x 27 cm x 15.2 cm  
Suspension adjust sizing: 6.5 - 8  
Suspensions: 4-point suspension may be converted to 6-point suspension with optional strap  
Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15  
Types: Type 1  
Classes: Class E, G, and C (Vented: Class C only)  
Optional features: hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

## Markings

Types: Type 1 offers protection to the top of the head  
Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection  
HV: meets all requirements for high visibility  
LT: provides protection at low temperatures -22°F  
HT: provides protection at high temperatures 140°F  
Date code: indicates month and year when the shell was molded – does not indicate service life



## Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use  
Never alter or modify the shell or suspension system  
Inspect the hard hat each time before use and replace if there is ANY sign of damage  
Replace hard hat after it receives a considerable impact  
Accessories such as liners have not been tested to the requirement of this standard  
Clean only with mild soap and lukewarm water  
Store hard hat in a clean, dry place that is out of direct sunlight  
Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat  
Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage