SL T2™ SAFETY HELMET







VENTED OPTIONS







ENGINEERED PROTECTION THAT SURROUNDS

Experience unparalleled protection with the SL T2 Safety Helmet. Featuring advanced EPS foam that absorbs impacts from all angles, coupled with a lightweight ABS shell. The helmet is compatible with SL T2 accessories for customized safety solutions. All-day comfort is ensured with strategically placed padding and effortless ratchet suspension adjustment. The 4-point cross-over chin strap secures the helmet for confident performance. Available in vented and non-vented options.



FEATURES

Advanced Impact Absorption: EPS foam liner absorbs forces from all angles for unparalleled protection

Robust, Lightweight Shell: ABS shell ensures durable, lightweight protection

Accessory Compatibility: Pair with SL T2 accessories for tailored safety solutions

Comfortable Padding: Designed with strategically placed soft padding to ensure all-day comfort

Effortless Adjustment: Ratchet suspension easily adjusts to provide a perfect fit across all head sizes

Secure-Fit Design: 4-point cross-over chin strap with quick-release buckle for a secure, comfortable fit

Engineered Toughness: Meets ANSI/ISEA Z89.1-2014 (R2019) Type II standard and EN 12492:2012 Energy Absorption and Retention System clauses to ensure durability and confidence in performance



SCAN HERE
TO EXPLORE THE
SL T2 HELMET
AND ACCESSORIES

SL T2™ SAFETY HELMET

ENGINEERED PROTECTION THAT SURROUNDS

Experience unparalleled protection with the SL T2 Safety Helmet. Featuring advanced EPS foam that absorbs impacts from all angles, coupled with a lightweight ABS shell. The helmet is compatible with SL T2 accessories for customized safety solutions. All-day comfort is ensured with strategically placed padding and effortless ratchet suspension adjustment. The 4-point cross-over chin strap secures the helmet for confident performance. Available in vented and non-vented options.













RATCHET SUSPENSION

VARIATIONS

NON-VENTED

Ratchet Suspension | 8 Variations

nateriet suspension o variations			
	HPT261110	White	
	HPT261111	Black	
	HPT261112	Gray	
	HPT261120	Red	
	HPT261130	Yellow	
	HPT261131	Hi-Vis Lime	
	HPT261140	Orange	
	HPT261162	Light Blue	



VENTED

Ratchet Suspension | 8 Variations

	HPT261110V	White
	HPT261111V	Black
	HPT261112V	Gray
	HPT261120V	Red
	HPT261130V	Yellow
	HPT261131V	Hi-Vis Lir
	HPT261140V	Orange
	HPT261162V	Light Blu



MATERIALS

Shell: ABS (Acrylonitrile Butadiene Styrene) Plastic

Inner Lining: Dual Density EPS (Expanded Polystyrene) Foam

Sweatband: Fleece + Foam

Chin Strap: Nylon + Silicone + PS (Polystyrene) + PP (Polypropylene)

Buckle: POM (Polyoxymethylene)

Suspension: PP (Polypropylene)

⚠ WARNING: Cancer and Reproductive Harm −P65Warnings.ca.gov

GENERAL SPECIFICATIONS

Weight: 510g
Shell Thickness: 2.5mm
Dimensions: 10.25" x 8.5" x 7"
Suspension Adjust Sizing: 65/8 to 77/8

Suspension: Adjustable with Ratcheting Wheel

Chin Strap: 4-Point Cross-Over Adjustable

MARKINGS

Standard: ANSI/ISEA Z89.1-2014 (R2019)

Type: Type II Safety Helmet

Class: Non-Vented — Class E (Electrical) Rated for 20,000 Volts, Vented — Class C (Conductive) Does Not Offer Electrical Protection

LT: Low Temperatures Protection up to -22°F

HT: High Temperatures Protection up to 140°F

Date Code: Indicates month and year shell was molded - does not indicate service life.

Product markings may vary // Updated as of 05.25

SL T2 Safety Helmet $^{\rm m}$ meets Energy Absorption Capacity clauses 4.2.1.2 (Front), 4.2.1.3 (Side), & 4.2.1.4 (Rear), and Retention System clauses 4.2.3 (Strength) & 4.2.4 (Effectiveness) of EN12492:2012

PRODUCT GUIDELINES

Maximum shelf life of 5 years (shell) from the time of first use - whichever occurs first.

Never alter or modify the shell, suspension, or chin strap.

Inspect the hard hat each time before use and replace immediately if there is any sign of damage.

Replace the helmet after it receives a considerable impact.

Only use genuine Pyramex accessories and replacement parts that have been approved for use with this helmet.

Clean only with mild soap and lukewarm water.

Store helmet in a clean, dry place that is out of direct sunlight.

Do not use paints, chemicals, adhesives, gasoline, or similar substances on the helmet.

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage.