



TruLock™ ANSI CE CSA



Dielectric
 Lightweight spectacle – 21 gm
 Patented temples lock into place

Part No.	Black Temples
ESB9510S ●●●	Clear
ESB9510ST ●●●	AF Clear H2X
ESB9520S ●●●	Gray
ESB9520ST ●●●	AF Gray H2X
ESB9530S ●●●	Amber
ESB9556S ●●●	Multi-Color Mirror
ESB9580S ●●●	I/O Mirror



Watch the video

vimeo.com/pyramex/trulock



Download a FREE QR Reader to your smartphone through your phone's app store
 Scan the code

TruLock Multi-Colors ANSI CE CSA

Sold in dozen quantity only

Comes with six assorted temple colors: red, blue, green, purple, orange and black

Multi-pack includes two of each temple color with clear lenses

Perfect for work areas where color coding is necessary

Part No.	Multi-Color Temples
ES9510SMP ●●●	Clear



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European EN166 (●) or Canadian CSA Z94.3 (●) – SEI third-party certification.

TruLock™

General Specifications

Weight: 21 gm
 Bridge: 11.3 curve
 Lens base: 9.5 curve
 Lens size diagonal: 132.7mm
 Lens size vertical: 44 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 157 mm
 Overall width (hinge - hinge): 130 mm
 Closest point between temple tips: 65 mm

Materials

Lens: polycarbonate
 Temples: nylon
 Hinge: nylon

Part No.	Lens Marking	Temple Marking
ESB9510S	2C - 1.2 P 1 F CE	CE P EN166 F
ESB9510ST	2C - 1.2 P 1 F N CE	CE P EN166 F
ESB9520S	5 - 2.5 P 1 F CE	CE P EN166 F
ESB9520ST	5 - 2.5 P 1 F N CE	CE P EN166 F
ESB9530S	2 - 1.2 P 1 F CE	CE P EN166 F
ESB9556S	5 - 2.5 P 1 F CE	CE P EN166 F
ESB9580S	5 - 1.7 P 1 F CE	CE P EN166 F
ES9510SMP	2C - 1.2 P 1 F CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Temple Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967