

AmpBT™

ANSI/ASA S3.19-1974

NRR 26dB

Ergonomically arched, cushioned headband for superior comfort // Four microphones // Amplifies hearing while suppressing harmful sounds and reducing them to a safe level // Bluetooth for wireless listening and cell phone use // Auto shut-off after four hours // 3.5mm AUX jack cord // 2 AAA batteries are included // Easy-adjust volume and ambient noise controls

- VGPME30BT Black
- VGPME31BT Desert Tan

Earmuff Breakdown

Headband: Polyurethane (PU)
Headband Adjustment: Steel Wire
Headband Cushion: Fabric and Polyvinyl chloride (PVC)
Ear Cup: Acrylonitrile-butadiene-styrene (ABS)
Ear Cushion: Polyvinyl chloride (PVC)
Volume knob: Thermoplastic elastomer (TPE)
Battery Compartment: Acrylonitrile-butadiene-styrene (ABS)

Measurements

Dimensions: 13.8cm x 16.5cm x 14cm
Earcup Thickness: 4cm
Weight: 304gm

Packaging

Capture Clam: 3 per box
Case: 24 per case

Product Guidelines

The level of noise entering a person's ear, when hearing protection is worn as directed is closely approximated by the difference between the A-weighted environmental level and the NRR.

- Example:
1. The environmental noise level at the ear is 92 dB(A).
 2. The NRR is 26 decibels (dB).
 3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.

i All hearing protection meets ANSI/ASA S3.19-1974 standards. For more information visit our website or contact your sales representative.



VGPME30BT



VGPME31BT