

Winch

Ref: SF-WN-801

- To be used for raising or lowering of personnel or material into confined spaces.
 - Equipped with bolting fixture for robust fitting on to the tripod SF-TP-800
 - Lifting load Capacity : 135 Kg.
 - Wire length : 20m, 25m, 30m & 40m.
 - As per EN 1496 : 2017 CLASS A.
 - To be used with a Retractable Fall Arrester when deployed for raising or lowering a person.
- Also available with the S.S. wire rope instead of galvanized rope. Respective references with S.S. wire rope shall be SF-WN-801(20SS), SF-WN-801(25SS), SF-WN-801(30SS) & SF-WN-801(40SS)



Model	Length	Weight
SF-WN-801(20)	20 m	8.190 kg.
SF-WN-801(25)	25 m	8.700 kg.
SF-WN-801(30)	30 m	10.800 kg.
SF-WN-801(40)	40 m	11.800 kg.

OPTIONAL ACCESSORIES WITH TRIPOD SF-TP-800A



Aluminum Single Pulley
With single side attachment
Ref: SF-5330



Double Pulley
With single side attachment
Ref: SF-FAP-1013



Turn Locking Karabiner
Ref: SF-1101 A
also available in captive eye pin
SF-1101A(C)



Steel Alloy Pulley
With single side attachment
Ref: SF-5331

TRIPOD KIT BAG



SF-KB-904



SF-KB-905

TRIPOD HEAD SHADE OPTIONS



Red



black



Green



Yellow



Blue