



DP1000 Series ANSI CE

Part No.

DP1000 •• PYDP1000\* •• PYDP1000BN\* •• \*Pyramex retail packaged product

**General Specifications** 

Noise reduction rating (NRR): 32dB Single Number Rating (SNR): 36 dB Restrictions of Hazardous Substances (RoHS) compliant Hearing protection style: uncorded plug Resusable: no Metal detectable: no Shape: tapered Size: one size fits most Plug color: hi-vis orange Plug dimension: 2.6 x 1.2 cm

## **Materials**

Plug: polyurethane foam

## **Product Guidelines**

The level of noise entering a person's ear, when hearing protection is worn as directed is closely approximated by the difference between the A-weighted environmental level and the NRR.

- Example: 1. The environmental noise level at the ear is 92 dB(A).
  - 2. The NRR is 32 decibels (dB).
  - 3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.

There's more to see at **PYRAMEXSAFETY.COM** 

(P) 800.736.8673 | (F) 901.861.4967

PDP1000BN

DP1000

All hearing protection meets ANSI S3.19 standards (•). Some options meet European (CE EN-352:2002) (•) standards. For more information visit our website or contact your sales representative.