

AVANTÉ®



Black Frame

| Part | Lens |
|----------|-----------------------|
| SB4510D• | Clear |
| SB4520D• | Gray |
| SB4530D• | Amber |
| SB4560D• | Infinity Blue |
| SB4570D• | Silver Mirror |
| SB4575D• | Blue Mirror |
| SB4580D• | Indoor/Outdoor Mirror |

Gun Metal Frame

| Part | Lens |
|-----------|-------|
| SGM4510D• | Clear |
| SGM4520D• | Gray |

Silver Frame

| Part | Lens |
|----------|-----------------------|
| SS4510D• | Clear |
| SS4520D• | Gray |
| SS4545D• | Ice Orange Mirror |
| SS4580D• | Indoor/Outdoor Mirror |
| SS4585D• | Ice Blue Mirror |

Silver and Black Frame

| Part | Lens |
|-----------|---------------|
| SSB4510D• | Clear |
| SSB4520D• | Gray |
| SSB4570D• | Silver Mirror |

Black Frame with Cord

| Part | Lens |
|-----------|-----------------------|
| SB4510DP• | Clear |
| SB4520DP• | Gray |
| SB4580DP• | Indoor/Outdoor Mirror |

Silver Frame with Cord

| Part | Lens |
|-----------|-------------------|
| SS4545DP• | Ice Orange Mirror |

- Straight back flexible temples.
- Vented frame increases air flow to prevent fogging.
- Anti-Scratch lenses offer 99.9% protection against harmful UV rays.
- Built-in rubber nose pads provide comfort fit and protect against slipping.
- Lightweight sports styling contours to the face to provide maximum protection.

PACKAGING

Polybag: 1pc


















Inner Box: 12 pcs





Case: 300 pcs

GENERAL SPECIFICATION

| |
|--|
| Bridge: 14.27mm |
| Closest Point Between Lens: 19.03mm |
| Closest Point Between Temples Tips: 101.26mm |
| Lens Base: 8 curve |
| Lens Size Diagonal: 76.48mm |
| Lens Size Vertical: 38.39mm |
| Lens Thickness: 2.4mm |
| Overall Length (Lens-Tip): 177mm |
| Overall Width (Hinge-Hinge): 136.65mm |
| PD: 64mm |
| Weight: 26.9g |

| COMPONENT | MATERIAL | FEATURES |
|-------------|-----------------|--|
| Temple Tips | Hard Rubber | N/A |
| Temple | Polycarbonate | N/A |
| Frame | Polycarbonate | 3 thin holes on the frame, one in the middle, one in left edge and one in the right edge |
| Lens | Polycarbonate | 8 base curve, cut lens attached to frame, lens half covered in left and right edge of lens |
| Nose Piece | Rubber | N/A |
| Screw | Stainless Steel | Standard hinge screw |

| PART | LENS | LENS MARKING | FRAME MARKING |
|----------|---|-----------------|---------------|
| SB4510D |  Clear | P Z87 + U6 | P Z87 + |
| SB4510DP |  Clear | P Z87 + U6 | P Z87 + |
| SB4520D |  Gray | P Z87 + U6 L3 | P Z87 + |
| SB4520DP |  Gray | P Z87 + U6 L3 | P Z87 + |
| SB4530D |  Amber | P Z87 + U6 | P Z87 + |
| SB4560D |  Infinity Blue | P Z87 + U6 L1.3 | P Z87 + |
| SB4570D |  Silver Mirror | P Z87 + U6 L3 | P Z87 + |
| SB4575D |  Blue Mirror | P Z87 + U6 L3 | P Z87 + |
| SB4580D |  Indoor/Outdoor Mirror | P Z87 + U6 L1.7 | P Z87 + |
| SB4580DP |  Indoor/Outdoor Mirror | P Z87 + U6 L1.7 | P Z87 + |
| SGM4510D |  Clear | P Z87 + U6 | P Z87 + |
| SGM4520D |  Gray | P Z87 + U6 L3 | P Z87 + |
| SSB4510D |  Clear | P Z87 + U6 | P Z87 + |
| SSB4520D |  Gray | P Z87 + U6 L3 | P Z87 + |
| SSB4570D |  Silver Mirror | P Z87 + U6 L3 | P Z87 + |
| SS4510D |  Clear | P Z87 + U6 | P Z87 + |
| SS4520D |  Gray | P Z87 + U6 L3 | P Z87 + |

| PART | LENS | LENS MARKING | FRAME MARKING |
|----------|---|-----------------|---------------|
| SS4545D |  Ice Orange Mirror | P Z87 + U6 L3 | P Z87 + |
| SS4545DP |  Ice Orange Mirror | P Z87 + U6 L3 | P Z87 + |
| SS4580D |  Indoor/Outdoor Mirror | P Z87 + U6 L1.7 | P Z87 + |
| SS4585D |  Ice Blue Mirror | P Z87 + U6 L3 | P Z87 + |

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact