

Capstone 500 Series **ANSI CE CSA AS BALLISTIC**

Fits over prescription glasses

Soft vinyl goggle body conforms to facial contours

Goggle provides protection against dust and chemical splash

Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance

GG504T and GG504TM passes D3: Droplet and Splash Test – provides protection from droplets and splashes

Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Part No.	Gray Body with Quick Release Strap
GG504T ●●●●	AF Clear H2X
GG504TM ●●●●	AF Clear H2MAX
Part No.	Chemical Green Body with Neoprene Strap
GC504TN ●●●●	AF Clear H2X



vimeo.com/pyramex/h2max

General Specifications

Weight: 92 gm
PD: 68 mm
Bridge: 45 mm
Lens base: 5.5 curve
Lens size diagonal: 154 mm
Lens size vertical: 78 mm
Lens thickness: 2.3 mm
Overall length (lens - tip): 91 mm
Overall width (hinge - hinge): 180 mm
Strap length: 540 mm

Materials

Lens: polycarbonate
Body: polycarbonate & polyvinyl chloride (PVC)
Headband: textile elastic
Nosepiece: polyvinyl chloride (PVC)

Part No.	Lens Markings	Frame Markings
GG504T	P Z87 + U6	P Z87 + D3 / P c SEI CAN/CSA Z94.3-15
GG504TM	P Z87 + U6	P Z87 + D3 / P c SEI CAN/CSA Z94.3-15
GC504TN	P Z87 + U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
UV Filter Transmittance
U6: .01% max effective far UV • .1% max near UV

Frame Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
D3: Droplet & Splash Test with strap
c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices