

CAPSTONE® RL

REPLACEABLE LENS GOGGLE



- Lens is interchangeable.
- Fits over prescription glasses.
- Indirect ventilation system prevents fogging.
- Includes interchangeable cloth and neoprene straps.
- Co-material goggle provides superior protection against dust entry and chemical splash.
- Thermoplastic (TPE) body with universal nose bridge is flexible and contours to the user's face.

Gray Goggle with Adjustable Neoprene Strap

Part	Lens
G804TRL • • • •	Clear H2X Anti-Fog
G824TRL • • • •	Gray H2X Anti-Fog

Part	Description
R8NEO	Replacement Neoprene Strap
R8CLO	Replacement Cloth Strap
R804T • • • •	Replacement Clear H2X Anti-Fog Lens
R824T • • • •	Replacement Gray H2X Anti-Fog Lens

GENERAL SPECIFICATION

Bridge: 41.3mm
Closest Point Between Strap Holding Parts: 165mm
Lens Base: 6 Curve
Lens Size Diagonal: 164mm
Lens Size Vertical: 74.4mm
Lens Thickness: 2.3mm
Strap Length: 540mm
Overall Width: 93mm
PD: 68mm
Weight: 79gm





CAPSTONE® RL

REPLACEABLE LENS GOGGLE

PACKAGING

Polybag: 1pc
 Inner box: 12pcs
 Case: 72pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6C base single lens
Hard Piece	PP	Co-material body with flexible soft flange contour to face
Soft Piece	TPE	
Strap Holder	Nylon	Strap clipped on the holder
Nose Piece	TPE	Universal, integral to frame body (soft piece)
Headband	Neoprene	Adjustable elastic strap

PART	LENS	LENS MARKING	FRAME MARKING
G804TRL	 Clear	P Z87 +	P Z87 + / P c SEI CAN/CSA Z94.3-07
R804T	 Clear	P Z87 +	N/A
G824TRL	 Gray	P Z87 +	P Z87 + / P c SEI CAN/CSA Z94.3-07
R824T	 Gray	P Z87 +	N/A

LENS MARKING**Symbols:**

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices