# Wrap-around sunglass style









**Black Frame** 

SB8575DT • •

Part Lens SB8510DT••

SB8510DT • Clear Anti-Fog
SB8515DT • Coffee Anti-Fog

SB8520DT • • Gray Anti-Fog

SB8580DT • Indoor/Outdoor Mirror Anti-Fog

Blue Mirror Anti-Fog

• Integrated nose piece.

- · Stylish straight back temples.
- Lightweight, contemporary frame.
- · Wrap-around sunglass style fits all facial sizes.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

#### White Frame

Part Lens

SW8520DT • Gray Anti-Fog

SW8575DT • Blue Mirror Anti-Fog

# GENERAL SPECIFICATION

Bridge: 13mm Lens Base: 8 Curve Lens Size Diagonal: 66mm

Lens Thickness: 2.0mm

Lens Size Vertical: 38.8mm

Overall Length (Lens-Tip): 145mm

Overall Width (Hinge-Hinge): 133+/-1mm

Weight: 35.6gm

Closest point between lens: 9mm

Closest point between temple tips: 95+/-5mm



PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base wrap around lens
Frame	Nylon	N/A
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8510DT	Clear Anti-Fog	P Z87 +	P Z 8 7 +
SB8515DT	Coffee Anti-Fog	P Z87 + S	P Z 8 7 +
SB8520DT	Gray Anti-Fog	P Z87 + S	P Z 8 7 +
SB8575DT	Blue Mirror Anti-Fog	P Z87 + S	P Z 8 7 +
SB8580DT	Indoor/Outdoor Mirror Anti-Fog	P Z87 + S	P Z 8 7 +
SW8520DT	Gray Anti-Fog	P Z87 + S	P Z 8 7 +
SW8575DT	Blue Mirror Anti-Fog	P Z87 + S	P Z 8 7 +

## **LENS MARKING**

#### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

- +: High Impact
- H: Small Head Size
- S: Special Purpose

#### **UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

#### **Visible Light Filters:**

L1.3: 85% Max. Visible Light L1.7: 55% Max. Visible Light L2.5: 29% Max. Visible Light L3: 18% Max. Visible Light

### FRAME MARKING

#### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact