

# G704T

Low Profile Goggle



Low Profile Goggle

Part Lens

G704T •••  Clear Anti-Fog

- Low profile, modern sport design with anti-glare frame.
- Direct ventilation prevents fogging.
- Adjustable elastic band and soft PVC frame.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

## GENERAL SPECIFICATION

Bridge: 21mm

Closest Point Between Lens: 18mm

Lens Base: 6 Curve

Lens Size Diagonal: 82mm

Lens Size Vertical: 52mm

Lens Thickness: 2mm - 2.2mm

Overall Width (Hinge-Hinge): 148mm

PD: 64mm

Weight: 35gm

## PACKAGING


Polybag: 1pc

Inner Box: 12 pcs

Case: 144 pcs

## G704T

COMPONENT	MATERIAL	FEATURES
Nose Piece	N/A	Integrated with PVC Frame
Frame	PVC	Low-profile frame design
Strap	N/A	Elastic Strap
Lens	Polycarbonate	6 base curve
Side Shields	N/A	Integrated with PVC Frame
Connector	Nylon	Thin and modern design

PART	LENS	LENS MARKING	FRAME MARKING
G704T	 Clear Anti-Fog	P Z87 + U6	P Z87 +

## LENS MARKING

**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

**UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

**Visible Light Filters:**

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

## FRAME MARKING

**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact