

IONIX™

LIGHTWEIGHT CONTEMPORARY FRAME



PART

SB8110D****

SB8110DT****

SB8120D****

SB8120DT****

LENS

Clear

Clear (Anti-Fog)

Gray

Gray (Anti-Fog)

PART

SB8116D****

SB8165D****

SB8170D****

SB8180D****

LENS

Sandstone Bronze

Ice Blue Mirror

Silver Mirror

Indoor/Outdoor Mirror

- Extreme style in safety eyewear, with clean lines and sports appeal.
- Ventilated, straight-back flexible temples provide cool, pressure-free fit.
- Built-in rubber nose piece provides all day comfort.
- Rubber temples tips keep eyewear secure for the active worker.
- Scratch-resistant polycarbonate lenses provides maximum vision protection, filter out 99.9% of harmful UV rays.

GENERAL SPECIFICATION

Bridge: 15mm

Closest Point Between Lens: 9mm

Closest Point Between Temple Tips: 92mm

Lens Base: 8 Curve

Lens Size Diagonal: 80mm

Lens Size Vertical: 40mm

Lens Thickness: 2.0mm

Overall Length (Lens-Tip): 125mm

Overall Width (Hinge-Hinge): 137mm

Weight: 26gm

PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

IONIX™

LIGHTWEIGHT CONTEMPORARY FRAME

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve, wrap around design
Frame	Nylon	Lightweight frame
Temple tips	TPR	Comfortable fit
Nose Piece	TPR	N/A
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8110D	 Clear	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8110DT	 Clear (Anti-Fog)	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8120D	 Gray	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8120DT	 Gray (Anti-Fog)	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8116D	 Sandstone Bronze	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8165D	 Ice Blue Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8170D	 Silver Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8180D	 Indoor/Outdoor Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices