



Provoq® ANSI CSA



RUBBER NOSEPIECE



RUBBER TIPS

Soft nosepiece

Rubber temples

Part No.	Lens and Temples
S7210S ●●	Clear
S7210ST ●●	AF Clear
S7220S ●●	Gray
S7220ST ●●	AF Gray
S7230S ●●	Amber
S7240S ●●	Orange
S7255S ●●	Multi-Color Mirror
S7260S ●●	Infinity Blue
S7270S ●●	Silver Mirror
S7275S ●●	Blue Mirror
S7280S ●●	I/O Mirror
S7280ST ●●	AF I/O Mirror
Part No.	Pink Temples
SP7210ST ●●	AF Clear



There's more to see at
PYRAMEXSAFETY.COM
 (P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet Canadian (CSA Z94.3) (◉) standards. For specific lens options visit our website or contact your sales representative.

Provoq®

General Specifications

Weight: 24.9 gm
 PD: 64 mm
 Bridge: 16.66 mm
 Lens base: 9 curve
 Lens size diagonal: 79.83 mm
 Lens size vertical: 41.12 mm
 Lens thickness: 2.4 mm
 Overall length (lens - tip): 158 mm
 Overall width (hinge - hinge): 136 mm
 Closest point between temple tips: 79.35 mm
 Closest point between lens: 8.18 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: plated steel
 Temple Tip: thermoplastic rubber (TPR)
 Nosepiece: thermoplastic rubber (TPR)

Part No.	Lens Markings	Frame Markings
S7210S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S7210ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S7220S	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-15
S7220ST	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-15
S7230S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S7240S	P Z87 + S	P Z87 +
S7255S	P Z87 + S	P Z87 +
S7260S	P Z87 + S	P Z87 +
S7270S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S7275S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S5880S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
S5880ST	P Z87 + U6 L1.7	P Z87 +
SP7210ST	P Z87 + U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L3: 18% Max. Visible Light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

