



## TruLock™ ANSI CE CSA



LOCKING  
TEMPLE



DIELECTRIC

Dielectric

Lightweight spectacle – 21 gm

Patented temples lock into place

Part No.	Black Temples
SB9510S ●●●	Clear
SB9510ST ●●●	AF Clear H2X
SB9520S ●●●	Gray
SB9520ST ●●●	AF Gray H2X
SB9530S ●●●	Amber
SB9556S ●●●	Multi-Color Mirror
SB9580S ●●●	I/O Mirror
SB9580ST ●●●	AF I/O Mirror



### Watch the video

[vimeo.com/pyramex/trulock](https://vimeo.com/pyramex/trulock)



Download a FREE QR Reader  
to your smartphone through  
your phone's app store

Scan the code

## TruLock Multi-Colors ANSI CE CSA

Sold in dozen quantity only

Comes with six assorted temple colors: red, blue, green, purple, orange and black

Multi-pack includes two of each temple color with clear lenses

Perfect for work areas where color coding is necessary

Part No.	Multi-Color Temples
S9510SMP ●●●	Clear



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European EN166 (●) or Canadian CSA Z94.3 (●) – SEI third-party certification.

## TruLock™

### General Specifications

Weight: 21 gm  
 Bridge: 11.3 curve  
 Lens base: 9.5 curve  
 Lens size diagonal: 132.7mm  
 Lens size vertical: 44 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 157 mm  
 Overall width (hinge - hinge): 130 mm  
 Closest point between temple tips: 65 mm

### Materials

Lens: polycarbonate  
 Temples: nylon  
 Hinge: nylon

Part No.	Lens Marking	Temple Marking
SB9510S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB9510ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB9520S	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB9520ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB9530S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB9556S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB9580S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB9580ST	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9510SMP	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 S: Special Purpose  
 Z87: ANSI standard for eye and face protection devices  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L1.7: 55% max visible light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967