

XS3 PLUS®

XSccessive Protection



PART

SB4610STP****

SB4620STP****

SB4630STP***

SB4680STP**

LENS

Clear (Anti-Fog)

Gray (Anti-Fog)

Amber (Anti-Fog)

Indoor/Outdoor Mirror (Anti-Fog)

- Slim Temples for custom fit.
- Soft foam padding provides comfort fit.
- Open temples allow clip on cord option for goggle-like fit.
- Sports-look Safety Spectacle with superior eye protection.
- Unique temple design with co-injection temple tips for cushion comfort.
- Foam padding and cord option provide seal to keep out dust and airborne particles.
- Lenses are coated for superior scratch resistance, provide 99% protection against harmful UV rays.

GENERAL SPECIFICATION

Bridge: 19.3mm

Closest Point Between Temple Tips: 79mm

Lens Base: 7 Curve

Lens Size Diagonal: 131mm

Lens Size Vertical: 50mm

Lens Thickness: 2.1mm

Overall Length [Lens-Tip]: 155mm

Overall Width [Hinge-Hinge]: 145mm

PD: 68mm

Weight: 34gm

PACKAGING

Polybag: 1pc

Inner Box: 12pcs

Outer Carton: 300pcs

XS3 PLUS®

XSccessive Protection

| COMPONENT | MATERIAL | FEATURES |
|--------------|-----------------|---|
| Lens | Polycarbonate | 7 base curve, wrap around design with side protection |
| Frame | Polyamide 66 | Rounded frame with good coverage |
| Side Shields | Polycarbonate | Integral to lens |
| Sponge | CR | Soft and comfortable |
| Nose Piece | Polycarbonate | Universal, integral to lens |
| Strap | Polyester | Soft and Flexible |
| Temple | Polycarbonate | Spatula with soft tip end |
| Temple Tip | TPE | Additionally co-injected with soft cushion tip |
| Hinge | Polycarbonate | 3 barrel type |
| Screw | Stainless Steel | Standard hinge screw |

| PART | LENS | LENS MARKING | FRAME MARKING |
|-----------|--|-----------------|------------------------------------|
| SB4610STP |  Clear (Anti-Fog) | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| SB4620STP |  Gray (Anti-Fog) | P Z87 + U6 L2.5 | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| SB4630STP |  Amber (Anti-Fog) | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| SB4680STP |  Indoor/Outdoor Mirror (Anti-Fog) | P Z87 + U6 L1.7 | P Z87 + / P c SEI CAN/CSA Z94.3-07 |

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

W: Welding Filter

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices