

Neshoba™ is one of the lightest weight spectacles on the market, weighing in at 16 grams. To eliminate the threats of an eye injury, an employer should provide workers with products that are comfortable and dependable.





NeshobaTM ANSI CE CSA

Frameless design with thin flexible temples

Ultra lightweight spectacle - 16 gm

Part No.	Black Temples	
S9710S • • •		Clear
S9710ST • • •	AF	Clear H2X
S9720S • • •		Gray
S9720ST • • •	AF	Gray H2X
S9730S • • •		Amber
S9780S • • •		I/O Mirror





Neshoba™

General Specifications

Weight: 16 gm PD: 64 mm Bridge: 12.3 mm Lens base: 9.5 curve

Lens size diagonal: 75.8 mm Lens size vertical: 43.3 mm Lens thickness: 1.6 mm

Overall length (lens - tip): 151 mm Overall width (hinge - hinge): 135 mm Closest point between temple tips: 78 mm Closest point between lens: 14.5 mm

Materials

Lens: polycarbonate Temples: polycarbonate Hinge: polycarbonate Screw: stainless steel

Part No.	Lens Markings	Frame Markings	
S9710S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15	
S9710ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15	
S9720S	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15	
S9720ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15	
S9730S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15	
S9780S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15	

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% max visible light

L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at PYRAMEXSAFETY.COM